

IFO-380cst

	UNITS	LIMIT	RME380	TEST METHOD REFERENCE
Kinematic viscosity at 50 °C	mm ² /S	max.	380,00	ISO 3104
Kinematic viscosity at 40 °C	mm ² /S	max.		ISO 3104
Kinematic viscosity at 40 °C	mm ² /S	min.		ISO 3104
Density at 15 °C	kg/m ³	max.	991,0	ISO 3675 or ISO 12185
CCAI		max.	870	
Flash point	°C	min.	60	ISO 2719
Pour point (upper)	°C	Winter	30	ISO 3016
Pour point (upper)	°C	Summer	30	ISO 3016
Cloud point	°C	max.		ISO 3015
Cetane index	-	min.		ISO 4264
Carbon residue: micro method on the 10 % volume distillation residue	mass %	max.		ISO 10370
Carbon residue: micro method	mass %	max.	18,00	ISO 10370
Ash	mass %	max.	0,10	ISO 6245
Hydrogen sulfide	mg/kg	max.	2,00	IP 570
Total sediment by hot filtration	mass %	max.	0,10	ISO 10307-1/2
Water	volume %	max.	0,50	ISO 3733
Sulfur	mass %	max.		ISO 8754 - ISO 14596
Vanadium	mg/kg	max.	350	IP 501, IP 470 or ISO 14597
Aluminium plus silicon	mg/kg	max.	60	IP 501, IP 470 or ISO 10478



Monjasa DMCC
United Arab Emirates
Tel: +971 4 420 8600
dubai@monjasa.com

Monjasa Pte. Ltd.
Singapore
Tel: +65 3163 4000
singapore@monjasa.com

Monjasa Inc.
United States
Tel: +1 203 276 6300
americas@monjasa.com

Monjasa A/S
Denmark (Fredericia)
Tel: +45 70 260 230
denmark@monjasa.com

Monjasa A/S
Denmark (Copenhagen)
Tel: +45 70 260 236
denmark@monjasa.com

Monjasa S.A.
Panama
Tel: +507 202 5231
americas@monjasa.com

Monjasa PTY S.A.
Panama
Tel: +507 202 5231
americas@monjasa.com

Monjasa Ltd.
Cyprus
Tel: +357 25 123 200
cyprus@monjasa.com

Monjasa Pty. Ltd.
Namibia
Tel: +264 64 201 2180
namibia@monjasa.com

IFO-180cst

	UNITS	LIMIT	RME180	TEST METHOD REFERENCE
Kinematic viscosity at 50 °C	mm ² /S	max.	180,00	ISO 3104
Kinematic viscosity at 40 °C	mm ² /S	max.		ISO 3104
Kinematic viscosity at 40 °C	mm ² /S	min.		ISO 3104
Density at 15 °C	kg/m ³	max.	991,0	ISO 3675 or ISO 12185
CCAI		max.	860	
Flash point	°C	min.	60	ISO 2719
Pour point (upper)	°C	Winter	30	ISO 3016
Pour point (upper)	°C	Summer	30	ISO 3016
Cloud point	°C	max.		ISO 3015
Cetane index	-	min.		ISO 4264
Carbon residue: micro method on the 10 % volume distillation residue	mass %	max.		ISO 10370
Carbon residue: micro method	mass %	max.	15,00	ISO 10370
Ash	mass %	max.	0,07	ISO 6245
Hydrogen sulfide	mg/kg	max.	2,00	IP 570
Total sediment by hot filtration	mass %	max.	0,10	ISO 10307-1/2
Water	volume %	max.	0,50	ISO 3733
Sulfur	mass %	max.		ISO 8754 - ISO 14596
Vanadium	mg/kg	max.	150	IP 501, IP 470 or ISO 14597
Aluminium plus silicon	mg/kg	max.	50	IP 501, IP 470 or ISO 10478



Monjasa DMCC
United Arab Emirates
Tel: +971 4 420 8600
dubai@monjasa.com

Monjasa Pte. Ltd.
Singapore
Tel: +65 3163 4000
singapore@monjasa.com

Monjasa Inc.
United States
Tel: +1 203 276 6300
americas@monjasa.com

Monjasa A/S
Denmark (Fredericia)
Tel: +45 70 260 230
denmark@monjasa.com

Monjasa A/S
Denmark (Copenhagen)
Tel: +45 70 260 236
denmark@monjasa.com

Monjasa S.A.
Panama
Tel: +507 202 5231
americas@monjasa.com

Monjasa PTY S.A.
Panama
Tel: +507 202 5231
americas@monjasa.com

Monjasa Ltd.
Cyprus
Tel: +357 25 123 200
cyprus@monjasa.com

Monjasa Pty. Ltd.
Namibia
Tel: +264 64 201 2180
namibia@monjasa.com